


primus

Rigid Mounted Industrial Washer Extractors

RS 13, 18, 27, 35



FEATURES

- Rigid mounted, medium spin
- Stainless steel cabinet (AISI 304)
- Stainless steel drum and tub
- Large drain valve (75 mm)
- Easy access to all parts
- Patented soap hopper and drain valve (Liqui-Mix® system)
- Frequency controlled motor
- Power Wash® perforated lifting ribs: more mechanical action, lower water consumption

OPTIONS

- Full control (FC) microprocessor
- Soft wash version (wet cleaning)
- Coin operated timer
- Anti-vandalism fascia panel
- Liquid soap pumps
- Water recovery kit
- LPMS networking software

liqui-mix®

POWERWASH®

TYPE		RS 13	RS 18	RS 27	RS 35
Drum diameter	mm	650	700	750	914
	inch	25,59	27,559	29,53	35,984
Drum depth	mm	392	468	610	505
	inch	15,42	18,42	24***	19,882
Volume (calc)	l	130	180	269,5	331,2
	gal	34,35	47,56	71,2	87,5
Load fill factor 1:10	kg	13	18	27	33,2
	lb	28,66***	39,76	59,5	73,2
RPM spin		525	505	490	510
G-force (calce)		100	100	100	133
Door opening	mm	406	406	505	505
	inch	16	16	19,88	19,88
Height	mm	by construction	1315	by construction	1450
	inch		51,77		57,1
Width	mm	750	855	860	1100
	inch	29,53	33,66	33,86	43,31
Voltage range		1-3phx208-240V*	1-3phx208-240V*	1-3phx208-240V*	1-3phx208-240V*
* Machine execution always single phase					
***Can be changed to lower for technical reasons					

The company Primus bvba preserves the right to change the machines and the specifications in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.

www.primuslaundry.com

primus

Quality **without**
compromise

